

Rohrreinigungsleitungen

mit Düse

Handverschraubung

Stecknippel

AG

M22 : 1/8"

M21 : 1/8"

KW : 1/8"

KW : 1/8"

K : 1/8"

M22 : 1/8"



Schläuche mit einer Drahteinlage und glatter Decke

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
Flexy	6	300 bar	100 °C	10 m	420 302 010	420 317 010	420 337 010	420 332 010	420 347 010		420 312 010	
				15 m	420 302 015	420 317 015	420 337 015	420 332 015	420 347 015		420 312 015	
				20 m	420 302 020	420 317 020	420 337 020	420 332 020	420 347 020		420 312 020	
				25 m	420 302 025	420 317 025	420 337 025	420 332 025	420 347 025		420 312 025	
				30 m	420 302 030	420 317 030	420 337 030	420 332 030	420 347 030		420 312 030	

Schläuche aus Kunststoff mit einer Gewebeeinlage

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
Polya	5	200 bar	20 °C	8 m	410 002 008	410 017 008	410 037 008	410 032 008		410 047 008	410 012 008	
				10 m	410 002 010	410 017 010	410 037 010	410 032 010		410 047 010	410 012 010	
				15 m	410 002 015	410 017 015	410 037 015	410 032 015		410 047 015	410 012 015	
				20 m	410 002 020	410 017 020	410 037 020	410 032 020		410 047 020	410 012 020	
				25 m	410 002 025	410 017 025	410 037 025	410 032 025		410 047 025	410 012 025	
				30 m	410 002 030	410 017 030	410 037 030	410 032 030		410 047 030	410 012 030	
Polya	5	120 bar	20 °C	40 m	410 002 040	410 017 040	410 037 040	410 032 040		410 047 040	410 012 040	
				10 m	400 002 010	400 017 010	400 037 010	400 032 010		400 047 010	400 012 010	
				15 m	400 002 015	400 017 015	400 037 015	400 032 015		400 047 015	400 012 015	
				20 m	400 002 020	400 017 020	400 037 020	400 032 020		400 047 020	400 012 020	
				25 m	400 002 025	400 017 025	400 037 025	400 032 025		400 047 025	400 012 025	
				30 m	400 002 030	400 017 030	400 037 030	400 032 030		400 047 030	400 012 030	

ohne Düse

HV : AG + O-Ring

AG : AG + O-Ringe

Stecknippel KW : AG + O-Ring

AG : AG + O-Ring

mit Düse

Rotationsdüse

M22 : 1/8"




M21 : 1/8"

1/8" : 1/8"

KW : 1/8"

M22 : 1/8"

KW : 1/8"



Schläuche aus Kunststoff mit einer Drahteinlage

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
R+M 1	4	300 bar	99 °C	10 m	411 000 010	411 015 010	411 040 010	411 035 010		411 010 010	411 037 010	411 038 010
				15 m	411 000 015	411 015 015	411 040 015	411 035 015		411 010 015	411 037 015	411 038 015
				20 m	411 000 020	411 015 020	411 040 020	411 035 020		411 010 020	411 037 020	411 038 020
				25 m	411 000 025	411 015 025	411 040 025	411 035 025		411 010 025	411 037 025	411 038 025
				30 m	411 000 030	411 015 030	411 040 030	411 035 030		411 010 030	411 037 030	411 038 030

Symbole DN Nennweite P Druck °C Temperatur ↔ Länge TYP Typ °C Temperatur