

Suttner Drehverschraubungen ST-44 (Swivel)

Handverschraubungen : Außengewinde



HV M22 : AG. Max. 400 bar / 150 °C



HV M21 : AG. Max. 400 bar / 150 °C



HV M22 : AG. Max. 200 bar

1/4"
3/8"
1/2"
M18
M22

R+M Nr.	I
568 00	54 mm
568 25	70 mm
568 26	73 mm
568 30	76 mm
568 10	76 mm

R+M Nr.	I
568 50	49 mm
568 70	46 mm

R+M Nr.	I
200 044 510	49 mm

HV M22 : M22 AG. Edelstahl.
Max. 400 bar / 150 °C

M22

R+M Nr.	I
568 19	56 mm

Handverschraubungen : Innengewinde



HV M22 : IG. Max. 400 bar / 150 °C



HV M21 : IG. Max. 400 bar / 150 °C

1/4"
3/8"

R+M Nr.	I
568 15	67 mm
568 20	68 mm

R+M Nr.	I
568 80	67 mm

Dichtungen ST-44



O-Ring



Nutting



O-Ring (hinten)



Stützring



Dichsatz

R+M Nr.	VPE
050 000 651	1
568 009 100	100

R+M Nr.
050 000 379

R+M Nr.	TYP
568 011	klein
568 010	groß

R+M Nr.	VPE
050 001 511	1
568 008 100	100

R+M Nr.
568 001 1

Symbole I Höhe O Gewinde VPE Verpackungseinheit TYP Typ