


Handverschraubungen passend für System 2000



HV M22 : AG. Max. 400 bar / 150 °C

R+M Nr.	Höhe
560 302	30 mm



HV M22 : IG. Max. 400 bar / 150 °C

R+M Nr.	Höhe
561 302	45 mm



HV M22 : AG. Max. 400 bar / 150 °C

R+M Nr.	Höhe
561 402	49 mm



HV M22 : IG. Max. 400 bar / 150 °C

R+M Nr.	Höhe
561 502	47 mm




HV M22 : AG. Max. 400 bar / 150 °C


R+M Nr.	Höhe
561 602	50 mm

Handverschraubungen US

Handverschraubungen US


HV M22 : IG.
Max. 400 bar / 150 °C


R+M Nr.	Höhe
561 501	45 mm


M22 : IG.
Max. 400 bar / 150 °C


R+M Nr.	Höhe
565 402	29


O-Ring, Handverschraubung US.
10,77x2,62, NBR 70

R+M Nr.	Höhe
903 825 00	


HV M22 : AG.
Max. 400 bar / 150 °C

R+M Nr.	Höhe
561 601	46 mm


M22 : AG.
Max. 400 bar / 150 °C

R+M Nr.	Höhe
565 302	29

Symbole Höhe Gewinde