

Hochdruckschnellkupplungen

Kupplungen CEJN 322 und Stecknippel



Kupplung : IG. Messing verchromt /
Stahl verchromt.
Max. 200 bar / 100 °C



Kupplung : IG. Messing verchromt /
Stahl verchromt. Mit Ventil.
Max. 200 bar / 100 °C



Kupplung : AG. Messing verchromt /
Stahl verchromt.
Max. 200 bar / 100 °C

⊙	DN
1/4"	7,4
3/8"	7,4
M18	7,4

R+M Nr.	I
552 001	48 mm
552 002	50 mm
552 008	84 mm

R+M Nr.	I
552 031	57 mm
552 032	57 mm

R+M Nr.	I
552 011	45 mm
552 012	47 mm
552 018	69 mm



Stecknippel : IG. Ø 12 mm. Stahl
vernickelt. Max. 200 bar / 100 °C



Stecknippel : AG. Ø 12 mm. Stahl
vernickelt. Max. 200 bar / 100 °C

⊙	DN
1/4"	7,4
3/8"	7,4
M18	7,4

R+M Nr.	I
552 101	36 mm
552 102	38 mm

R+M Nr.	I
552 111	36 mm
552 112	38 mm
552 108	56 mm

Kupplungen SP-20 150 bar und Stecknippel



Kupplung : IG. Messing.
Max. 150 bar / 100 °C



Kupplung : AG. Messing.
Max. 150 bar / 100 °C



Stecknippel : IG. Ø 14,8 mm. Stahl
verzinkt. Max. 150 bar / 100 °C

⊙	DN
1/4"	8,0
3/8"	8,0
1/2"	8,0

R+M Nr.	I
550 10	41 mm
550 30	42 mm

R+M Nr.	I
550 20	43 mm

R+M Nr.	I
551 11	40 mm
551 10	40 mm



Stecknippel : AG. Ø 14,8 mm. Stahl
verzinkt. Max. 150 bar / 100 °C



O-Ring, TYP SP-20. 13,1x2,6.
Max. 150 bar / 100 °C

⊙	DN
3/8"	8,0

R+M Nr.	I
551 20	43 mm

R+M Nr.	I
790 60	