

Schlauchadapter



M22 IG : M22 AG. K 2000. Messing.
Max. 400 bar

R+M Nr.
565 66



Stecknippel 10 mm : M22 AG.
Max. 250 bar

R+M Nr.
559 910 2



Steckkupplung 10 mm : 3/8" AG.
Max. 400 bar

R+M Nr.
559 910 1



Steckkupplung 11 mm. Max. 400 bar

R+M Nr.	
559 911 12	1/2" AG
559 911 38	3/8" AG
559 911 22	M22 AG
559 911 23	HV M22




Kupfer Dichtungsscheibe. K 2000

R+M Nr.	Ø
781 519 1	18,8 mm



O-Ring

R+M Nr.	Ø
790 55	10 mm
790 57	11 mm



Stützring

R+M Nr.	Ø
790 58	10 mm
790 59	11 mm



HV M22 : M22 AG. Edelstahl.
Max. 400 bar / 150 °C

R+M Nr.	Ø
568 19	M22



Stecknippel 11 mm : M22 AG.
Max. 400 bar

R+M Nr.	l
316 961 1	190 mm



Stecknippel 11 mm : M22 AG.
Max. 400 bar

R+M Nr.	l
316 961 2	145 mm
316 961 3	150 mm



M27 AG : AG. Messing *.
Max. 400 bar

R+M Nr.	Ø
318 271 8	M18
318 272 1	M21



M24 AG : 3/8" IG. Messing *.
Max. 400 bar

R+M Nr.
318 24



Stecknippel 10 mm : M22 AG.
Max. 210 bar

R+M Nr.	l
316 951 0	190 mm



M22 AG : Stecknippel. Messing.
Max. 250 bar / 100 °C

R+M Nr.	l
559 908 221	104 mm



M24 AG : AG. Messing *.
Max. 400 bar

R+M Nr.	Ø
318 241 8	M18
318 242 1	M21



O-Ring

R+M Nr.	Ø
903 598 00	M27



O-Ring

R+M Nr.	Ø
791 42	M24



M27 AG : 3/8" IG. Messing *.
Max. 400 bar

R+M Nr.
318 27

* nicht zulässig für patentierte WAP / Venturi - Einsätze