

## Suttner Rotordüsen mit Keramikeinsatz

ST-456



1/4" IG. Spritzwinkel 20°.  
200 - 350 bar. Max. 100 °C



Kit ST-456



M18 IG. Spritzwinkel 20°.  
200 - 350 bar. Max. 100 °C



Kit ST-456

ST-558



1/4" IG. 300 - 500 bar. Max. 90 °C



Kit ST-558

| R+M Nr.     | D   | C        |
|-------------|-----|----------|
| 200 456 530 | 03  | gelb     |
| 200 456 535 | 035 | lila     |
| 200 456 540 | 04  | braun    |
| 200 456 545 | 045 | hellgrün |
| 200 456 550 | 05  | schwarz  |
| 200 456 555 | 055 | hellblau |
| 200 456 560 | 06  | rot      |
| 200 456 565 | 065 | natur    |
| 200 456 570 | 07  | rosa     |
| 200 456 580 | 08  | orange   |
| 200 456 590 | 09  | grün     |

| R+M Nr.     | D | C |
|-------------|---|---|
| 200 456 130 |   |   |
| 200 456 135 |   |   |
| 200 456 140 |   |   |
| 200 456 145 |   |   |
| 200 456 150 |   |   |
| 200 456 155 |   |   |
| 200 456 160 |   |   |
| 200 456 165 |   |   |
| 200 456 170 |   |   |
| 200 456 180 |   |   |
| 200 456 190 |   |   |

| R+M Nr.     | D   | C        |
|-------------|-----|----------|
| 200 456 630 | 03  | gelb     |
| 200 456 635 | 035 | lila     |
| 200 456 640 | 04  | braun    |
| 200 456 645 | 045 | hellgrün |
| 200 456 650 | 05  | schwarz  |
| 200 456 655 | 055 | hellblau |
| 200 456 660 | 06  | rot      |
| 200 456 665 | 065 | natur    |
| 200 456 670 | 07  | rosa     |
| 200 456 680 | 08  | orange   |
| 200 456 690 | 09  | grün     |

| R+M Nr.     | D | C |
|-------------|---|---|
| 200 456 130 |   |   |
| 200 456 135 |   |   |
| 200 456 140 |   |   |
| 200 456 145 |   |   |
| 200 456 150 |   |   |
| 200 456 155 |   |   |
| 200 456 160 |   |   |
| 200 456 165 |   |   |
| 200 456 170 |   |   |
| 200 456 180 |   |   |
| 200 456 190 |   |   |

| R+M Nr.     | D  | C       |
|-------------|----|---------|
| 200 558 530 | 03 | gelb    |
| 200 558 540 | 04 | braun   |
| 200 558 550 | 05 | schwarz |
| 200 558 560 | 06 | rot     |
|             |    |         |
|             |    |         |
|             |    |         |
|             |    |         |
|             |    |         |
|             |    |         |

| R+M Nr.     | D | C |
|-------------|---|---|
| 200 558 130 |   |   |
| 200 558 140 |   |   |
| 200 558 150 |   |   |
| 200 558 160 |   |   |
|             |   |   |
|             |   |   |
|             |   |   |
|             |   |   |
|             |   |   |
|             |   |   |

ST-458.1



1/4" IG. Spritzwinkel 20°.  
120 - 250 bar. Max. 100 °C



Kit ST-458.1



1/2" IG. Spritzwinkel 20°.  
120 - 250 bar. Max. 100 °C



Kit ST-458.1

| R+M Nr.     | D  | C |
|-------------|----|---|
| 200 458 811 | 11 |   |
| 200 458 812 | 12 |   |
| 200 458 813 | 13 |   |
| 200 458 815 | 15 |   |
| 200 458 818 | 18 |   |
| 200 458 820 | 20 |   |
| 200 458 825 | 25 |   |
| 200 458 830 | 30 |   |

| R+M Nr.     | D | C |
|-------------|---|---|
| 200 458 311 |   |   |
| 200 458 312 |   |   |
| 200 458 313 |   |   |
| 200 458 315 |   |   |
| 200 458 318 |   |   |
| 200 458 320 |   |   |
| 200 458 325 |   |   |
| 200 458 330 |   |   |

| R+M Nr.     | D   | C        |
|-------------|-----|----------|
| 200 458 745 | 045 | hellgrün |
| 200 458 755 | 055 | hellblau |
| 200 458 770 | 07  | rosa     |
| 200 458 791 | 09  | grün     |
| 200 458 712 | 12  |          |
| 200 458 715 | 15  |          |
| 200 458 720 | 20  |          |
| 200 458 730 | 30  |          |

| R+M Nr.     | D | C |
|-------------|---|---|
| 200 458 245 |   |   |
| 200 458 255 |   |   |
| 200 458 270 |   |   |
| 200 458 290 |   |   |
| 200 458 312 |   |   |
| 200 458 315 |   |   |
| 200 458 320 |   |   |
| 200 458 330 |   |   |

## Suttner Rotordüsen mit Hartmetalleinsatz

ST-559



1/4" IG. 300 - 600 bar. Max. 90 °C



Kit ST-559

| R+M Nr.     | D   | C |
|-------------|-----|---|
| 200 559 520 | 02  |   |
| 200 559 530 | 03  |   |
| 200 559 540 | 04  |   |
| 200 559 550 | 05  |   |
| 200 559 555 | 055 |   |
| 200 559 560 | 06  |   |
|             |     |   |
|             |     |   |
|             |     |   |
|             |     |   |

| R+M Nr.     | D | C |
|-------------|---|---|
| 200 559 120 |   |   |
| 200 559 130 |   |   |
| 200 559 140 |   |   |
| 200 559 150 |   |   |
| 200 559 155 |   |   |
| 200 559 160 |   |   |
|             |   |   |
|             |   |   |
|             |   |   |
|             |   |   |

Symbole D Düse C Farbkodierung