

Umlaufventile

VB75



☰ = Eingang 1/2" IG. ☱ = Ausgang 3/8" IG.
Umlaufventil mit Hohlsschraube. Banjo-Anschluss.
X: 19 mm. Y: 62-73 mm. Passend IP50, IP44, IP47,
IP60, IP63 / Speck NP16. Max. 250 bar / 90 °C

R+M Nr.	☐	☐
532 093 0	30 l/min	

VB85



☰ = Eingang 1/2" IG. ☱ = Ausgang 1/2" IG.
☐ = Bypass 1/2" IG. Max. 90 °C

R+M Nr.	☐	☐
532 851 6	max. 160 bar	80 l/min
532 852 8	max. 280 bar	80 l/min

VB80



☰ = Eingang 1/2" IG. ☱ = Ausgang 1/2" IG.
☐ = Bypass 1/2" IG.
Edelstahl.
Max. 90 °C

R+M Nr.	☐	☐
532 802 84	max. 280 bar	80 l/min

VB80/150



☰ = Eingang 1/2" IG. ☱ = Ausgang 1/2" IG.
☐ = Bypass 1/2" IG. ☐ = Manometer 1/4" IG.
Max. 90 °C

R+M Nr.	☐	☐
532 801 50	max. 150 bar	80 l/min

VB53/500



☰ = Eingang 1/2" IG. ☱ = Ausgang 1/2" IG. ☐ =
Bypass 1/2" IG.
Max. 90 °C

R+M Nr.	☐	☐
532 535 00	max. 500 bar	80 l/min

VB26



☰ = Eingang 1/2" IG. ☱ = Ausgang 1/2" IG.
Edelstahl.
Max. 90 °C

R+M Nr.	☐	☐
532 226 280	max. 280 bar	80 l/min

Symbole ☰ Eingang ☱ Ausgang ☐ Bypass ☐ Manometer ☐ Durchfluss ☐ Druck