



Knickschutz

Elastomer



Mit einer Lippe, die hinter der Fassung einrastet und dadurch ein Lösen verhindert.

Spezialwerkstoff, der wesentlich UV- und ozonbeständiger als herkömmlicher Gummi ist.

DN	Ø
6	15,5 mm
8	19,5 mm
10	20,5 mm
12	23,5 mm
12	23,5 mm bluflood

Neu



Schwarz

R+M Nr.
308 505
308 605
308 705
308 765



Blau

R+M Nr.
308 515
309 055
309 155
309 165
309 166 01 *



Grau

R+M Nr.
309 005
309 105



Gelb

R+M Nr.
308 805
308 905
309 185



Rot

R+M Nr.
308 855
308 955
309 175

* FDA-Konform und 1935 / 2004 / EG (lebensmittelrechtlich unbedenkliche Kunststoffe)


Andere Farben des gewellten Knickschutzes liefern wir auf Anfrage.

Gummi



Schwarz

R+M Nr.
308 60
308 70
308 76



Schwarz

R+M Nr.
308 50



Gelb

R+M Nr.
308 80
308 90



Blau

R+M Nr.
309 05
309 15
309 16



Blau

R+M Nr.
308 51



Grau

R+M Nr.
309 00
309 10



Grau

R+M Nr.
308 53

Kunststoff



Schwarz

R+M Nr.	Ø
308 52	13,5 mm



Spirale schwarz

R+M Nr.	Ø
308 55	14,5 mm



Spirale blau

R+M Nr.	Ø
308 551	14,5

Scheuerschutzspiral



Kunststoff. Ø 20 mm

R+M Nr.	VPE
308 491 620	per Meter
308 491 621	Rolle à 20 m

Einsätze für Stecknippel



Für Stecknippel pistolenseitig

R+M Nr.	DN
316 960 6	6
316 960 8	8